
SATCOM ANTENNA



DM SE109 SERIES PORTABLE UHF ANTENNA SYSTEM

The DM SE109-1 portable UHF Satcom antenna system is the latest innovation in high gain, lightweight portable manpack antennas from a proven manufacturer. The DM SE109-1 combines the high reliability and maximum portability of the DM C120 umbrella antenna system with an increase in antenna gain over the satellite frequency band of 244 to 318 MHz. A rapidly deployable antenna extension has been added to ensure reliable communications regardless of satellite intercept angle or atmospheric condition.

Design improvements, in addition to the gain enhancement, include:

- An input connector with a pigtail cable to allow for easy access and cost effective repair.
- Improved ground plane.
- Improved tripod antenna adjustment interface.

	CAI	

	Frequency Range		240 – 400 MHz
	VSWR		1.5:1
	Gain	Basic Antenna	+7.0 dBic nominal
종		with Antenna Extensions	+8.5 dBic at 244 MHz
ELECTRI			+11.0 dBic at 318 MHz
	Power		200 Watts
	Polarization		R.H.C.P.
	Impedance		50 Ohms
	3 dB Beamwi	dth	85 degrees (Nominal)

MECHANICAL	Input Connector	BNC Male
	Deployment Time	Less than one min
	Weigth (System)	6 lbs (Nominal)
	Operating Temperature	-25°F to +160°F
	Storage Temperature	-54°F to +250°F
Ħ	Wind Loading	80 MPH with Ballast
	Color	Lusterless Black
	Cable Length	12.5'

SYSTEM COMPONENTS

DM C120-6-1	Antenna
DM TS3-1-1	Tripod
DM U244-1-1	Antenna Extensions
DM CC5-2-1	Carrying Case
DM 1100015-001	Cables (2)

SATCOM ANTENNA

DM SE109 SERIES PORTABLE UHF ANTENNA SYSTEM

(700.9)

OUTLINE DIMENSIONS Inches (Centimeters) 24.25 (61.60) 18.3 REF (46.48)18.5 (46.99)14.54 REF (36.93)10.54 REF 6.0 DIA (26.77)(15.24) **DM C120-6-1 OUTLINE** STORED **CONFIGURATION** 15.88 SQ (403.2)TWIST/ **INTERLOCK DM U244-1-1 OUTLINE** 27.59